




No	Part	Description	Property	Details
	Body of board			
		Steel	Painted	Black color as default
		For indoor only		
		Dimensions	650/500/280 [mm]	High/Width/Deep.
		Connection of pipeline	DN25 (BSP 1")	From below
	Pump			
		Panther 72, or P72	Flow up to 70 Liter/min.	
		Filter of impurity	30um	Available
		Power supply	230 VAC ~	Single phase
		Power consumption	Less than 1KW	P72 – 0,6KW
	Flowmeter			
		K600/3 pulser		
		Accuracy	+/- 0,5%	
	Hose			
		4 r.meter 1" (DN25)		Available 6 and 8 r.meter
		Arm with swivels		Movable X&Y axis
	Nozzle			
		MD120 , Spout 1& 1/16"	Automatic shut off	Default
		Xide-80 Spout 15/16"	Automatic shut off	Available
		Xide-60 Spout 13/16"	Automatic shut off	Available
	Electronics			
		Main board SKiRT-L1/DS		Temperature of work between -40°C and +85°C
		Calibration method	Electronic only	
		Summary counter	Electronic	
		Access control	YES	iButton reader built -in
		Authorization method	Electronic iButtons	iButton 1-wire standard
		Max amount of drivers and cars	Up to 1000	Freely divided between drivers & cars
			10 iButtons is included	10 iButtons is included

		Desktop iButton reader for PC computer	Included	
		Identification cars & drivers	YES,	Process of authorization by single iButtons is available. Easy to change by the administrator.
		Security PIN Code	YES	Default is OFF. Easy to change by administrator.
		Data to be registered	Drivers & users	
			Cars & vehicles	
			Odometers(mileage)	Up to 7 digits, taped by user
			Bus line number	Up to 4 digits, taped by user
			Fuel dispensed quantity	Up to 9 999 Liters per transaction. Precision 0,01 Liter
			Number of transaction	Transactions numbers are incremented
		Cache memory	700	For fueling transaction
	Data transmission			
		RS 232	Standard	USB<>RS232 converter for PC included 
		RS 422/485	Optional	
		Analog modem AT	Optional	
		GSM terminal	Optional	For GSM-CSD protocol for P2P connection
		GSM-GPRS terminal	Optional	For GPRS protocol for connection to the Internet
		Ethernet TCP/IP	Optional	For Local Network connection
		WiFi –Lan TCP/IP	Optional	For wireless to LAN connection
	Printer for receipt			
		YES,	Optional	Width of receipt 57mm

	Computer software		Included	
		SKiRT Professional	For MS Windows	XP recommend
		Language version	English	Version for other language can be prepared on special request
		Database license	Included	Borland Database Engine for Paradox Tables
		Limit of drivers	NO LIMIT	
		Limit of cars	NO LIMIT	
		Subgroups of drivers	YES, NO LIMIT	
		Subgroups for cars	YES, NO LIMIT	
		Filters of data	YES	
		Data ordering	YES	
		Rich reports	YES	
		Export the data	YES	
			To Excel	
			To open format as text	ASCII Delimiter
		Reports formats		
			Directly on paper	
			PDF format	
			HTML, Internet WEB site format	